

Speedfit Oxy 100



Instructions fixed to the inside lid to prevent loss on site



4 Digit easy to read display

The Speedfit Oxy 100 Welding Purge Analyser kit comes complete and is ready to use straight out of the box. The unit is self-calibrating, and thus requires no adjustment prior to use. Simply switch on and it is ready to use.

The analyser measures Oxygen levels in the purged weld area, letting the operator know exactly when it is safe to begin welding. This will result in reduction in waiting time and the amount of purge gas used as well as producing high quality oxide free welds.

Its small handheld design makes it highly portable and so can be used in the fabrication workplace or out on site.

Kit comes complete with:

Analyser

1 Metre hose with flow adaptor

Stainless steel probe

Aspirator bulb

Carry case

Instructions

Calibration Certificate

Measuring Range: 20.9% to 0.01% (100ppm)

Sensor response: T90 < 15 seconds

Operating temperature: 10 to +40 Degrees C

Power Source: P3 9

Volt battery (Approx. 4000 hours usage)

Warranty: Sensor 18 months Electronics 2 years



Handy size

PCES Limited

Unit 20

Wulfrun Trading Estate

Stafford Road

Wolverhampton

WV10 6HH

Tel: 01902 713402 E-mail: martin@pces.uk.com

